

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

BORMAX Diesel Zusatz

Other means of identification:

Diesel Additive, BORMAX Additives for Diesel

Article No.:

10001

UFI:

PE7D-E69J-5PMJ-2QUC

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Fuel additive

Relevant identified uses:

Life cycle stage [LCS]

IS: Use at industrial sites

PW: Widespread use by professional workers

C: Consumer use

Product Categories [PC]

PC 13: Fuels

Process categories [PROC]

PROC 16: Use of fuels

Article categories [AC]

AC 1: Vehicles

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

UNEX GmbH

Erwin Schrödinger Strasse 9

2100 Korneuburg

Austria

Telephone: +43 1 375 00 34

E-mail: office@unex.co.at

Website: www.unex.co.at

1.4. Emergency telephone number

Vergiftungsinformationszentrale (VIZ), 24h: +43 1 406 43 43, +43 1 406 68 98 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	Calculation method.
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	Calculation method.
Carcinogenicity (<i>Carc. 2</i>)	H351: Suspected of causing cancer. (...)	Calculation method.
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	Calculation method.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS07

Exclamation mark



GHS08

Health hazard



GHS09

Environment

Signal word: Danger

hazard statements for health hazards

H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer. (...)

Hazard statements for environmental hazards

H411	Toxic to aquatic life with long lasting effects.
------	--

Supplemental hazard information: -

Precautionary statements Prevention

P202	Do not handle until all safety precautions have been read and understood.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/....

Precautionary statements Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/....
-------------	--

Precautionary statements Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
-------------	--

2.3. Other hazards

No data available

SECTION 3: Composition / information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP] Classification according to 67/548/EEC	Concentration
EC No.: 919-284-0 REACH No.: 01-2119463588-24	Kohlenwasserstoffe, C10,Aromaten >1%, Naphtalin Aquatic Chronic 2 (H411), Asp. Tox. 1 (H304), Carc. 2 (H351), STOT SE 3 (H336) Danger	48 - ≤ 81 weight-%

Full text of R-, H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Provide fresh air. Get medical advice/attention if you feel unwell.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing.

Following ingestion:

Rinse mouth. Let water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell. Do NOT induce vomiting. Observe risk of aspiration if vomiting occurs. Get immediate medical advice/attention.

Self-protection of the first aider:

Use personal protection equipment. First aider: Pay attention to self-protection!

4.2. Most important symptoms and effects, both acute and delayed

Pneumonia Pulmonary oedema Dizziness Dizziness

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet alcohol resistant foam Foam Carbon dioxide (CO₂) Dry extinguishing powder

Unsuitable extinguishing media:

Full water jet

5.2. Special hazards arising from the substance or mixture

In case of fire may be liberated: Carbon monoxide

Hazardous combustion products:

In case of fire: Carbon dioxide (CO₂) Carbon monoxide

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8).

Advices on general occupational hygiene

When using do not eat, drink or smoke. Avoid contact with eyes and skin.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
CH	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ⑤ (kann über die Haut aufgenommen werden)
BE	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (53 mg/m ³) ② 15 ppm (80 mg/m ³) ⑤ (peut être absorbé par la peau)
PL	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 20 mg/m ³ ② 50 mg/m ³ ⑤ (może przenikać przez skórę do organizmu)
NO	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
HTP (FI)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 1 ppm (5 mg/m ³) ② 2 ppm (10 mg/m ³)
LT	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ⑤ (Kancerogeninés)
SE	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ③ 15 ppm (80 mg/m ³)
NPEL (SK)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ② 15 ppm (80 mg/m ³)
TRGS 900 (DE)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 0.4 ppm (2 mg/m ³) ② 1.6 ppm (8 mg/m ³) ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden)
ES	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (53 mg/m ³) ② 15 ppm (80 mg/m ³) ⑤ (puede ser absorbido a través dérmica)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
IOELV (EU)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
VLA (FR)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³)
SI	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 50 mg/m ³ ② 50 mg/m ³ ⑤ (frakcija ki jo je mogoče vdihniti računati je treba z možnos tjo prodiranja skozi kožo)
HU	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 50 mg/m ³
NL	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 50 mg/m ³ ② 80 mg/m ³
MAK (AT)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (50 mg/m ³) ⑤ (kann über die Haut aufgenommen werden)
SI	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm ② 10 ppm ⑤ (računati je treba z možnostjo prodiranja skozi kožo)
ACGIH (US)	naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	① 10 ppm (52 mg/m ³) ② 15 ppm (79 mg/m ³) ⑤ (may be absorbed through the skin)
ACGIH (US)	Sulfonic acids, petroleum, sodium salts CAS No.: 68608-26-4 EC No.: 271-781-5	① 5 mg/m ³
BE	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m ³) ② 15 ppm (101.2 mg/m ³)
NO	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (68 mg/m ³)
HTP (FI)	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (68 mg/m ³)
LT	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m ³) ② 15 ppm (101.2 mg/m ³) ⑤
SE	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (68 mg/m ³) ② 15 ppm (101 mg/m ³)
NPEL (SK)	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m ³) ② 15 ppm (101.2 mg/m ³)
WEL (GB)	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m ³) ② 15 ppm (101.2 mg/m ³)
VRI (FR)	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m ³) ② 15 ppm (101.2 mg/m ³)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
MAK (AT)	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	② 15 ppm (101.2 mg/m ³) ⑤ (max. 4x15 min./Schicht)
TRGS 900 (DE)	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67 mg/m ³) ② 15 ppm (100.5 mg/m ³) ⑤ (Aerosol und Dampf)
HU	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 67.5 mg/m ³ ② 101.2 mg/m ³
ES	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m ³) ② 15 ppm (101.2 mg/m ³) ⑤ VLI,r
IOELV (EU)	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m ³) ② 15 ppm (101.2 mg/m ³)
SI	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m ³) ② 15 ppm (101.2 mg/m ³)
CH	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67 mg/m ³) ② 15 ppm (101 mg/m ³)
MAK (AT)	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m ³)
NL	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 50 mg/m ³ ② 100 mg/m ³ ⑤ (kan door de huid in het lichaam worden opgenomen)
ACGIH (US)	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 10 ppm (67.5 mg/m ³) ⑤ (inhalable fraction and vapor)
PL	2-(2-butoxyethoxy)ethanol CAS No.: 112-34-5 EC No.: 203-961-6	① 67 mg/m ³ ② 100 mg/m ³

8.1.2. Biological limit values

No data available

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route ③ Exposure time
Kohlenwasserstoffe, C10,Aromaten >1%, Naphtalin EC No.: 919-284-0	7.5 mg/kg	① DNEL worker ② Acute - inhalation, systemic effects ③ 24 h
Kohlenwasserstoffe, C10,Aromaten >1%, Naphtalin EC No.: 919-284-0	100 mg/m ³	① DNEL worker ② Long-term - inhalation, local effects

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Further information: see technical data sheet.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

8.2.2. Personal protection equipment



Eye/face protection:

Eye glasses with side protection EN 166

Skin protection:

Tested protective gloves must be worn EN ISO 374 Suitable material: Breakthrough time: min In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

Respiratory protection:

Respiratory protection necessary at: insufficient ventilation insufficient exhaust prolonged exposure Handling larger quantities According to experience this refers to the following tasks: Sampling Filling and transfer Suitable respiratory protection apparatus: Filtering device (EN 147) Particle filter device (EN 143)

8.2.3. Environmental exposure controls

Further information: see technical data sheet. Fresh air (open windows and doors) is necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: golden

Odour: Hydrocarbons, aromatic

Safety relevant basis data

parameter		at °C	Method	Remark
pH	not applicable			
Melting point	not determined			
Freezing point	not determined			
Initial boiling point and boiling range	> 190 - < 210 °C		ASTM D86	
Decomposition temperature	not determined			
Flash point	= 67.5 °C		ASTM D93	
Evaporation rate	not determined			
Auto-ignition temperature	not determined			
Upper/lower flammability or explosive limits	not determined			
Vapour pressure	not determined			
Vapour density	not determined			
Density	= 0.9 g/cm ³	20 °C		
Relative density	not determined			
Bulk density	not determined			
Water solubility	not determined			
Partition coefficient: n-octanol/water	not determined			
Dynamic viscosity	not determined			
Kinematic viscosity	= 1.33 cSt	20 °C		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

This material is considered to be non-reactive under normal use conditions.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

10.2. Chemical stability

No hazardous reaction when handled and stored according to provisions.

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Substance name	Toxicological information
Kohlenwasserstoffe, C10,Aromaten >1%, Naphtalin EC No.: 919-284-0	LC₅₀ Acute inhalation toxicity (vapour): >4,688 mg/l 4 h (Rat) LD₅₀ oral: >5,000 mg/kg (Rat) LD₅₀ dermal: >2,000 mg/kg (Rat)
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	LD₅₀ dermal: >2,000 mg/kg LC₅₀ Acute inhalation toxicity (vapour): >0.4 mg/l LD₅₀ oral: 533 mg/kg

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Suspected of causing cancer.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

May be fatal if swallowed and enters airways.

Additional information:

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

Substance name	Toxicological information
Kohlenwasserstoffe, C10,Aromaten >1%, Naphtalin EC No.: 919-284-0	EC₅₀ : >3 - <10 mg/l 2 d (Algae/water plant, Daphnia magna (Big water flea)) LC₅₀ : >2 - <5 mg/l 4 d (fish, Oncorhynchus mykiss (Rainbow trout)) NOEC : =1 mg/l 3 d (Algae/water plant, Pseudokirchneriella subcapitata) EC₅₀ : >1 - <3 mg/l 3 d (Algae/water plant, Pseudokirchneriella subcapitata)
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	EC₅₀ : 3 - 10 mg/l LC₅₀ : 2 - 5 mg/l NOEC : 1 mg/l EC₅₀ : 1 - 3 mg/l

Aquatic toxicity:

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Substance name	Biodegradation	Remark
Kohlenwasserstoffe, C10,Aromaten >1%, Naphtalin EC No.: 919-284-0	Yes, rapidly	Leichte biologische Abbaubarkeit. Dauer 28 Tage Abgebaut 58%
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	Yes, rapidly	

12.3. Bioaccumulative potential

No data available

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

Substance name	Results of PBT and vPvB assessment
Kohlenwasserstoffe, C10,Aromaten >1%, Naphtalin EC No.: 919-284-0	This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.
naphthalene CAS No.: 91-20-3 EC No.: 202-049-5	—

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

SECTION 14: Transport information

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1. UN number or ID number			
UN 3082	UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name			
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C3-C6 Alkylbenzene)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C3-C6 Alkylbenzene)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C3-C6 Alkylbenzene)	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (C3-C6 Alkylbenzene)
14.3. Transport hazard class(es)			
 9	 9	 9	 9
14.4. Packing group			
III	III	III	III
14.5. Environmental hazards			
		 MARINE POLLUTANT	
14.6. Special precautions for user			
Special provisions: 274 335 375 601 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Hazard identification number (Kemler No.): 90 Classification code: M6 tunnel restriction code: (-) Remark:	Special provisions: 274 335 375 601 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 Classification code: M6 Remark:	Special provisions: 274 335 969 Limited quantity (LQ): 5 L Excepted Quantities (EQ): E1 EmS-No.: F-A, S-F Remark:	Special provisions: A97 A158 A197 A215 Limited quantity (LQ): Y964 Excepted Quantities (EQ): E1 Remark:

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 22 Oct 2021

Print date: 22 Oct 2021

Version: 1



BORMAX Diesel Zusatz

15.1.2. National regulations

 [DE] National regulations

Water hazard class

WGK:

2 - deutlich wassergefährdend

15.2. Chemical Safety Assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Classification according to Regulation (EC) No 1272/2008 [CLP]:

Hazard classes and hazard categories	Hazard statements	Classification procedure
Aspiration hazard (<i>Asp. Tox. 1</i>)	H304: May be fatal if swallowed and enters airways.	Calculation method.
STOT-single exposure (<i>STOT SE 3</i>)	H336: May cause drowsiness or dizziness.	Calculation method.
Carcinogenicity (<i>Carc. 2</i>)	H351: Suspected of causing cancer. (...)	Calculation method.
Hazardous to the aquatic environment (<i>Aquatic Chronic 2</i>)	H411: Toxic to aquatic life with long lasting effects.	Calculation method.

16.5. Relevant R-, H- and EUH-phrases (Number and full text)

Hazard statements	
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H351	Suspected of causing cancer. (...)
H411	Toxic to aquatic life with long lasting effects.

16.6. Training advice

No data available

16.7. Additional information

No data available