

# Antifreeze 48

Nitrite-, phosphate-, amine -free

Antifreeze 48 is a premium radiator protection agent. This radiator protection agent utilises so-called hybrid technology. Inorganic and organic inhibitors are responsible for corrosion protection in the cooling system.

Appearance: green/blue

Suitable for aluminium engines, protects against frost, rust, overheating and deposits. Contains stabilisers that protect the coolant, prevents foaming. Application: Premix Radiator Protection AF48 G11 with water according to the mixing table and pour into the cooling circuit.

Spec:

Porsche/Audi/VW/Seat/Skoda TL 774 C, Mercedes DBL 7700, Ford ESD M97 B49, MAN 324 Typ NF, GM US 6277 M, Ford WSS-M97B44-C, Chrysler MS 9176, BMW N 600 69.0, VOLVO (Reg. No 260), Ford ESD M97 B49-A, OPEL GM QL 130100

Antifreeze	Water	frost protection
1 Part	1 Part	-37°C
1 Part	1,5 Part	-26°C
1 Part	2 Parts	-17°C

The coolant additive content should be at least 33%, as corrosion protection cannot be guaranteed below this level.

**ingredients:** Monoethylenglykol

Safety: See safety data sheet

Store in a cool, well-ventilated place. For further information on health, safety and environmental protection, see safety data sheet. Disclaimer This technical data sheet is the result of careful testing and is intended to advise our customers. The information contained herein is correct to the best of our knowledge. However, as we have no influence on the correct application, we can only accept liability for the perfect quality of the products supplied by us at the time of delivery. We reserve the right to make changes to this product information at any time in the light of new findings.