

Antifreeze 30

Nitrite-, phosphate-, amine- & silicate-free

Antifreeze 30 a premium radiator protection agent. This radiator protection agent utilises so-called OAT technology. Organic salts are responsible for protecting against radiator corrosion.

Appearance: pink

Suitable for lifetime filling in grey cast iron and all-aluminium engines. Provides year-round protection against frost, corrosion damage and limescale build-up. Increases the boiling point, maintains the cooling system and add-on parts. Radiator protection SF30 G12+ in OAT technology for all vehicles for which silicate-free products are prescribed. Tailored to the requirements of leading car manufacturers.

Spec:

Porsche/Audi/VW/Seat/Skoda TL 774 F, Mercedes MB 325.3, Ford ESE M97B49-A, Renault 41-01-00, Ford WSS-M97B44-D, Chrysler MS 9176, Ford ESD M97 B49- A, VOLVO (Reg. NDeutz/MWN 0199-2091 2 Auflage (C.W.) o 260), Ford ESD M97 B49-A, OPEL GM QL 130100, John Deere H 24 B1 und C1

Antifreeze	Water	frost protection
1 Part	1 Part	-37°C
1 Part	1,5 Part	-26°C
1 Part	2 Parts	-17°C

The coolant additive content should be at least 33%, as corrosion protection cannot be guaranteed below this level.

Ingredients: Monoethylenglykol

Safety: See safety data sheet

Store in a cool, well-ventilated place. For further information on health, safety and environmental protection, see safety data sheet. Disclaimer This technical data sheet is the result of careful testing and is intended to advise our customers. The information contained herein is correct to the best of our knowledge. However, as we have no influence on the correct application, we can only accept liability for the perfect quality of the products supplied by us at the time of delivery. We reserve the right to make changes to this product information at any time in the light of new findings.