



Smooth Running Engine Oil UNEX ENGINE OIL SAE 10W40 (Car)

PROPERTIES

UNEX Engine Oil SAE 10W40 is a fuel-efficient engine oil of SAE class 10W-40.

Base oils based on the latest synthesis technology, selected additives and very shear stable VI improvers ensure that the specified viscosity class is maintained over the entire oil life. Reliable cold starting even at low temperatures and high-temperature resistance under extreme loads are guaranteed. Cleaning additives prevent deposits, pistons and valves remain clean and guarantee the highest permissible oil residence time.

Selected additives permanently neutralize acidic combustion products, effectively protect the engine from corrosion and wear.

APPLICATION INFORMATION

UNEX Engine Oil SAE 10W40 is recommended for passenger car gasoline and diesel engines, including turbo-diesel and catalytic converter versions. **UNEX Engine Oil SAE 10W40** corresponds to the former ACEA A3/B3.

CERTIFICATES AND STANDARDS

- SAE 10W-40 • API SL/CF
- MB 229.1 • VW 501 01 / 505 00



UNEX Engine Oil SAE 10W40 is a product of UNEX GmbH - **MADE IN AUSTRIA**

Typical Properties	Unit	Test Method	UNEX ENGINE OIL- SAE 10W40
SAE Class		SAE J 300	10W-40
Density @ 15°C	g/cm ²	DIN 51 757	0,874
Kin. Viscosity @ 40°C	mm ² /s	DIN EN ISO 3104	95-98
Kin. Viscosity @ 100°C	mm ² /s	DIN EN ISO 3104	14-14,5
Viscosity Index (VI)		DIN ISO 2909	145-150
Flash Point COC	°C	DIN ISO 2592	230
Pour Point	°C	DIN ISO 3016	-30

The figures given may vary within the usual commercial range.

PACKAGING

