



Special High Performance Smooth Running Engine Oil UNEX ENGINE OIL SAE 5W30 C4

PROPERTIES

UNEX Engine Oil SAE 5W30 C4 is a modern high-performance fuel-economy engine oil of SAE grade 5W-30 based on state-of-the-art synthesis technology.

Excellent cold-start behavior ensures optimum lubrication reliability in the cold-running phase. Extreme loads and high temperatures are safely managed under all operating conditions. It ensures extremely high wear protection and significantly reduced friction losses.

By significantly saving fuel, UNEX Engine Oil SAE 5W30 C4 helps protect the environment by reducing emissions.

APPLICATION INFORMATION

UNEX Engine Oil SAE 5W30 C4 is a top product specially designed for use in the latest passenger car diesel engines, where the use is required according to Renault specification RN 0720 or Mercedes-Benz specification MB 226.51. In addition, UNEX Engine Oil SAE 5W30 C4 can be used in all vehicles with engine oil specification ACEA C3 and ACEA C4, as well as Mercedes-Benz specification MB 229.51. The modern Low Ash technology protects against ash deposits in the diesel particulate filter and thus improves its effectiveness and service life.

CERTIFICATES AND STANDARDS

- SAE 5W-30 • ACEA C3 / C4
- Renault RN 0720 • MB 226.51 • MB 229.51

UNEX Engine Oil SAE 5W30 C4 is a product of UNEX GmbH - **MADE IN AUSTRIA**

Typical Properties	Unit	Test Method	UNEX ENGINE OIL SAE 5W30 C4
SAE Class		SAE J 300	5W-30
Density @ 15°C	g/cm ³	DIN 51 757	0,851
Kin. Viscosity @ 40°C	mm ² /s	DIN EN ISO 3104	68-69
Kin. Viscosity @ 100°C	mm ² /s	DIN EN ISO 3104	11,7-12
Viscosity Index (VI)		DIN ISO 2909	172-174
Flash Point COC	°C	DIN ISO 2592	232
Pour Point	°C	DIN ISO 3016	-40

The figures given may vary within the usual commercial range.

PACKAGING

