



Special High Performance Smooth Running Engine Oil

UNEX ENGINE OIL SAE 0W30 950

PROPERTIES

UNEX ENGINE OIL SAE 0W30 950 is an extremely fuel-efficient high-performance engine oil of SAE grade 0W-30 based on state-of-the-art synthesis technology.

Excellent cold-start behavior ensures optimum lubrication reliability in the cold-running phase. Extreme loads and high temperatures are safely managed under all operating conditions. It ensures extremely high wear protection and significantly reduced friction losses.

With significant fuel savings, UNEX Engine Oil SAE 0W30 950 helps protect the environment by reducing emissions.

APPLICATION INFORMATION

UNEX Engine Oil SAE 0W30 950 is a top-quality product specially developed for use according to Ford specification WSS- M2C950-A in the new Ford TDCI Duratorq Euro 6 engines (from 2014) with exhaust aftertreatment and turbocharger.

UNEX Engine Oil SAE 0W30 950 can be used according to manufacturer specifications at extended change intervals up to 30,000 km, but is not backward compatible with older Ford specifications.

UNEX Engine Oil SAE 0W30 950 can also be used in engines where engine oils according to ACEA A5/B5 are required.

STANDARDS

- SAE 0W-30 • ACEA C2
- Ford WSS-M2C950-A • Fiat 9.55535-GS1/DS1 • Land Rover STJLR 03.1007 • PSA B71 2312



UNEX ULTRA A1 SAE 0W30 is a product of UNEX GmbH - **MADE IN AUSTRIA**

Typical Properties	Unit	Test Method	UNEX ENGINE OIL SAE 0W30 950
SAE Class		SAE J 300	0W-30
Density @ 15°C	g/cm ³	DIN 51 757	0,852
Kin. Viscosity @ 40°C	mm ² /s	DIN EN ISO 3104	50-52
Kin. Viscosity @ 100°C	mm ² /s	DIN EN ISO 3104	9,5-10
Viscosity Index (VI)		DIN ISO 2909	175-178
Flash Point COC	°C	DIN ISO 2592	230
Pour Point	°C	DIN ISO 3016	-40

The figures given may vary within the usual commercial range.

PACKAGING



1
LITER



5
LITER



20
LITER



60
LITER



208
LITER



1000
LITER