



Transmission Oil For Continuously Variable Automatic Transmissions (CVT) UNEX GEAR Fluid ATF CVT

PROPERTIES

UNEX Gear ATF CVT is a gear oil for continuously variable automatic transmissions (CVT) based on selected base oils of the latest synthesis technology and a powerful additive package. UNEX Gear ATF CVT is a universal ATF for use in continuously variable transmissions with steel push link belts or chains.

It offers very good wear, corrosion and oxidation protection for reliable function and longest service life, as well as high friction value stability.

APPLICATION INFORMATION

UNEX Gear ATF CVT is a multifunctional ATF for use in continuously variable transmissions (CVT) of most Japanese passenger cars.

UNEX Gear ATF CVT is not suitable for use in DCT/DSG, Hybrid CVT's (Honda/Ford) or stepped automatic transmissions.

CERTIFICATES AND STANDARDS

• Audi Multitronic • VW TL 521 80 (G 052 180) • Nissan NS-1, NS-2, NS-3 • Mitsubishi Diaqueen CVTF-J1 • BMW Mini Cooper EZL799 • Mitsubishi Diaqueen • Punch CVT Daihatsu Ammix CVT DFE • Mitsubishi Diaqueen CVTF-J4 and J4+ • Shell Green 1V • VW TL 521 16 (G 052 516) • Daihatsu Ammix CVT Fluid DC • MB 236.20 SP-III (CVT model only) • Subaru iCVT • Mazda JWS 3320 • Daihatsu Ammix CVT Fluid DFC • Toyota CVTF FE • Subaru iCVT FG • Toyota CVTF TC 1 • Dodge / Jeep / Chrysler NS-2 • Idemitsu CVTS-EX • Subaru ECVT • Dodge / Chrysler / Jeep Mopar CVT+4 • Subaru Lineartronic chain CVT and CVT II Fluid • GM / Saturn DEX-CVT • Subaru Lineartronic High Torque (HT) CVT Fluid • Honda HMMF (without starting clutch) • Suzuki CVTF TC • Honda HCF2 • Suzuki CVTF 3320 • Honda Z-1 (CVT model, without starting clutch), • Suzuki NS-2 not SFU for 2001 – 2007 Honda Fit & Jazz) • Suzuki CVT Green 1&2 • Hyundai / KIA SP III (CVT model)



UNEX GEAR ATF CVT is a product of UNEX GmbH. - **MADE IN AUSTRIA**

Typical Properties	Unit	Test Method	UNEX GEAR ATF CVT
SAE Class	g/cm ²	DIN 51 757	0,847
Density @ 15°C	mm ² /s	DIN EN ISO 3104	31-33
Kin. Viscosity @ 40°C	mm ² /s	DIN EN ISO 3104	6,90-7,10
Kin. Viscosity @ 100°C		DIN ISO 2909	170-172
Viscosity Index (VI)	°C	DIN ISO 2592	209
Flash Point COC	°C	DIN ISO 3016	-48
Pour Point			

The figures given may vary within the usual commercial range.

PACKAGING



1
LITER



5
LITER



20
LITER



60
LITER



208
LITER



1000
LITER