

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 1/11

Scheibenenteiser

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name/designation:

Scheibenenteiser

UFI:

6W6V-7S9K-3KD7-31V4

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture:

Antifreeze agent

1.3. Details of the supplier of the safety data sheet

Supplier (manufacturer/importer/only representative/downstream user/distributor):

ACS Chem GmbH

Labor

Erwin Schrödinger Strasse 9

2100 Korneuburg

Austria

Telephone: +43226223903

E-mail: office@acs-chem.at

Website: www.acs-chem.at

E-mail (competent person): office@acs-chem.at

1.4. Emergency telephone number

ACS Chem GmbH, 24h: +43 1 406 43 43, +43226223903 (Only available during office hours.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 1</i>)	H224: Extremely flammable liquid and vapour.	On basis of test data.
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	Calculation method.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms:



GHS02
Flame



GHS07
Exclamation mark

Signal word: Danger

Hazard statements for physical hazards	
H224	Extremely flammable liquid and vapour.
Hazard statements for health hazards	
H319	Causes serious eye irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 2/11

Scheibenenteiser

Supplemental hazard information: none

Precautionary statements Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.

Precautionary statements Response

P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statements Storage

P403 + P235	Store in a well-ventilated place. Keep cool.
-------------	--

Special rules for supplemental label elements for certain mixtures:

66,3 % percent of the mixture consists of ingredient(s) of unknown acute toxicity (dermal).

2.3. Other hazards

No data available

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients / Hazardous impurities / Stabilisers:

Product identifiers	Substance name Classification according to Regulation (EC) No 1272/2008 [CLP]	Concentration
CAS No.: 64-17-5 EC No.: 200-578-6 REACH No.: 01-2119457610-43-XXXX	ethanol Eye Irrit. 2 (H319), Flam. Liq. 2 (H225)  Danger Acute Toxicity Estimate ATE (oral) 10,740 mg/kg ATE (inhalation, vapour) 124.7 mg/L	39 - < 70 weight-%
CAS No.: 107-21-1 EC No.: 203-473-3 REACH No.: 01-2119456816-28	ethane-1,2-diol Acute Tox. 4 (H302), STOT RE 2 (H373)  Warning Acute Toxicity Estimate ATE (oral) 1,600 mg/kg ATE (dermal) ≥ 3,500 mg/kg ATE (inhalation, vapour) > 2.5 mg/L ATE (inhalation, dust/mist) ≥ 2.5 mg/L	5 - ≤ 9.84 weight-%

Full text of H- and EUH-phrases: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information:

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible). Remove victim out of the danger area. Remove contaminated, saturated clothing. If unconscious but breathing normally, place in recovery position and seek medical advice. Do not leave affected person unattended.

Following inhalation:

Provide fresh air. In case of respiratory tract irritation, consult a physician.

In case of skin contact:

After contact with skin, wash immediately with plenty of water and soap. If skin irritation or rash occurs: Get medical advice/attention.

After eye contact:

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 3/11

Scheibenenteiser

Following ingestion:

Rinse mouth. Let 1 glass of water be drunken in little sips (dilution effect). Get medical advice/attention if you feel unwell.

Self-protection of the first aider:

Use personal protection equipment.

4.2. Most important symptoms and effects, both acute and delayed

Serious eye damage/eye irritation

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

Water spray jet alcohol resistant foam Extinguishing powder Carbon dioxide (CO₂)

5.2. Special hazards arising from the substance or mixture

Combustible

Hazardous combustion products:

In case of fire: Gases/vapours, toxic

5.3. Advice for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

5.4. Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Personal precautions:

Remove persons to safety.

Protective equipment:

Wear protective gloves/protective clothing/eye protection/face protection.

6.1.2. For emergency responders

Personal protection equipment:

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow to enter into surface water or drains.

6.3. Methods and material for containment and cleaning up

For containment:

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

6.5. Additional information

Use appropriate container to avoid environmental contamination.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Protective measures

Advices on safe handling:

Wear personal protection equipment (refer to section 8).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 4/11

Scheibenenteiser

Fire prevent measures:

Keep away from sources of ignition - No smoking.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff. Avoid contact with skin, eyes and clothes.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures and storage conditions:

Keep container tightly closed in a cool, well-ventilated place.

Storage class (TRGS 510, Germany): 3 – Flammable liquids

7.3. Specific end use(s)

No data available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. Occupational exposure limit values

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
NO	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 500 ppm (950 mg/m ³)
NPEL (SK) from 23 Nov 2011	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 500 ppm (960 mg/m ³) ② 1,000 ppm (1,920 mg/m ³)
NL from 1 Jan 2023	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 137 ppm (260 mg/m ³) ② 1,000 ppm (1,900 mg/m ³) ⑤ (kankerverwekkend, kan door de huid in het lichaam worden opgenomen) H
MAK (AT)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³)
MAK (AT)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	② 2,000 ppm (3,800 mg/m ³) ⑤ (max. 3x60 min./Schicht, Momentanwert)
BG	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 mg/m ³
BE	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,907 mg/m ³)
VLA (FR)	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 1,000 ppm (1,900 mg/m ³) ② 5,000 ppm (9,500 mg/m ³)
SI from 4 Dec 2018	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 500 ppm (960 mg/m ³) ② 1,000 ppm (1,920 mg/m ³) ⑤ Y
TRGS 900 (DE) from 29 Mar 2019	ethanol CAS No.: 64-17-5 EC No.: 200-578-6	① 200 ppm (380 mg/m ³) ② 800 ppm (1,520 mg/m ³) ⑤ DFG, Y
BE	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ③ 40 ppm (104 mg/m ³) ⑤ (Aérosol, peut être absorbé par la peau) D, M

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 5/11

Scheibenenteiser

Limit value type (country of origin)	Substance name	① Long-term occupational exposure limit value ② Short-term occupational exposure limit value ③ Instantaneous value ④ Monitoring and observation processes ⑤ Remark
NO from 1 Jul 2021	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (damp og Aerosol, kan absorberes gjennom huden) HE5S
TRGS 900 (DE)	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 ppm (26 mg/m ³) ② 20 ppm (52 mg/m ³) ⑤ (Aerosol und Dampf, kann über die Haut aufgenommen werden) DFG, EU, H, Y, 11
NPEL (SK) from 23 Nov 2011	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (rátajte so vstrebávaním cez pokožku) K
MAK (AT)	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 ppm (26 mg/m ³) ⑤ (kann über die Haut aufgenommen werden) H
MAK (AT)	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	② 20 ppm (52 mg/m ³) ⑤ (max. 8x5 min./Schicht, Momentanwert, kann über die Haut aufgenommen werden) H
BG from 6 Jan 2012	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (трябва да се очаква абсорбиране през кожата)
IOELV (EU)	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (may be absorbed through the skin)
VRI (FR)	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (peut être absorbé par la peau)
SI	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (računati je treba z možnostjo prodiranja skozi kožo) K, Y, EU1
NL from 1 Jan 2023	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 20 ppm (52 mg/m ³) ② 40 ppm (104 mg/m ³) ⑤ (damp, kan door de huid in het lichaam worden opgenomen) H
NL	ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3	① 10 mg/m ³ ⑤ (deeltjes)

8.1.2. Biological limit values

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 6/11

Scheibenenteiser

8.1.3. DNEL-/PNEC-values

Substance name	DNEL value	① DNEL type ② Exposure route
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	950 mg/m ³	① DNEL worker ② Long-term - inhalation, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	114 mg/m ³	① DNEL Consumer ② Long-term - inhalation, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	1,900 mg/m ³	① DNEL worker ② Acute - inhalation, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	950 mg/m ³	① DNEL Consumer ② Acute - inhalation, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	343 mg/kg bw/ day	① DNEL worker ② Long-term - dermal, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	206 mg/kg bw/ day	① DNEL Consumer ② Long-term - dermal, systemic effects
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	87 mg/kg bw/ day	① DNEL worker ② Long-term - oral, systemic effects

Substance name	PNEC Value	① PNEC type
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	0.96 mg/L	① PNEC aquatic, freshwater
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	0.79 mg/L	① PNEC aquatic, marine water
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	580 mg/L	① PNEC sewage treatment plant
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	3.6 mg/kg	① PNEC sediment, freshwater
ethanol CAS No.: 64-17-5 EC No.: 200-578-6	0.63 mg/kg	① PNEC soil

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No data available

8.2.2. Personal protection equipment

Eye/face protection:

Eye glasses with side protection EN 166

Skin protection:

Tested protective gloves must be worn EN ISO 374 Suitable material: Breakthrough time: min In the case of wanting to use the gloves again, clean them before taking off and air them well. Breakthrough times and swelling properties of the material must be taken into consideration.

8.2.3. Environmental exposure controls

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 7/11

Scheibenenteiser

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state: Liquid

Colour: blue

Odour: Lemon

flammability: Yes

Safety relevant basis data

Parameter	Value	at °C	① Method ② Remark
pH	No data available		
Melting point	No data available		
Freezing point	No data available		
Initial boiling point and boiling range	No data available		
Flash point	≥ 17 °C		① DIN EN ISO 2719
Evaporation rate	No data available		
Auto-ignition temperature	No data available		
Upper/lower flammability or explosive limits	No data available		
Vapour pressure	No data available		
Vapour density	No data available		
Density	≈ 0.91 kg/L	20 °C	
Bulk density	not applicable		
Water solubility	No data available		
Dynamic viscosity	No data available		
Kinematic viscosity	No data available		

9.2. Other information

No data available

SECTION 10: Stability and reactivity

10.1. Reactivity

Extremely flammable liquid and vapour.

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

No data available

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

Gases/vapours, toxic

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

ethanol CAS No.: 64-17-5 EC No.: 200-578-6

LD₅₀ oral: 10,740 mg/kg (RATTE)

LC₅₀ Acute inhalation toxicity (vapour): 124.7 mg/L 4 h (RATTE)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 8/11

Scheibenenteiser

ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3

LD₅₀ oral: 1,600 mg/kg (rabbit)

LD₅₀ dermal: ≥3,500 mg/kg (Mouse)

LC₅₀ Acute inhalation toxicity (vapour): >2.5 mg/L 6 h (Rat)

LC₅₀ Acute inhalation toxicity (dust/mist): ≥2.5 mg/L 6 h (Rat)

Acute oral toxicity:

Based on available data, the classification criteria are not met.

Acute dermal toxicity:

Based on available data, the classification criteria are not met.

Acute inhalation toxicity:

Based on available data, the classification criteria are not met.

Skin corrosion/irritation:

Based on available data, the classification criteria are not met.

Serious eye damage/irritation:

Causes serious eye irritation.

Respiratory or skin sensitisation:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity:

Based on available data, the classification criteria are not met.

Carcinogenicity:

Based on available data, the classification criteria are not met.

Reproductive toxicity:

Based on available data, the classification criteria are not met.

STOT-single exposure:

Based on available data, the classification criteria are not met.

STOT-repeated exposure:

Based on available data, the classification criteria are not met.

Aspiration hazard:

Based on available data, the classification criteria are not met.

Additional information:

No data available

11.2. Information on other hazards

No data available

SECTION 12: Ecological information

12.1. Toxicity

ethanol CAS No.: 64-17-5 EC No.: 200-578-6

LC₅₀: 15,400 mg/L 4 d (fish)

LC₅₀: 5,012 mg/L 2 d (crustaceans)

EC₅₀: 12,700 mg/L 2 d (fish)

EC₅₀: >10,000 mg/L 2 d (crustaceans)

ErC₅₀: 22,000 mg/L 4 d (Algae/water plant)

LC₅₀: 1,806 mg/L

EC₅₀: >10,000 mg/L 2 d

ErC₅₀: 675 mg/L 4 d (Algae/water plant)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 9/11

Scheibenenteiser

ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3

LC₅₀: ≈72,860 mg/L 4 d (fish, Pimephales promelas (fathead minnow))

EC₅₀: >100 mg/L 2 d (Algae/water plant, Daphnia magna (Big water flea))

LC₅₀: >100 mg/L 4 d (Leuciscus idus)

EC₅₀: >100 mg/L 2 d (Daphnia magna)

EC₅₀: >100 mg/L 3 d

LC₅₀: 18,000 mg/L 4 d (Oncorhynchus mykiss (Rainbow trout))

ErC₅₀: <13,000 mg/L 4 d (Algae/water plant)

12.2. Persistence and degradability

ethanol CAS No.: 64-17-5 EC No.: 200-578-6

Biodegradation: —

ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3

Biodegradation: Yes, rapidly

12.3. Bioaccumulative potential

ethanol CAS No.: 64-17-5 EC No.: 200-578-6

Log K_{OW}: -0.35

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

ethanol CAS No.: 64-17-5 EC No.: 200-578-6

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

ethane-1,2-diol CAS No.: 107-21-1 EC No.: 203-473-3

Results of PBT and vPvB assessment: This substance does not meet the PBT/vPvB criteria of REACH, Annex XIII.

12.6. Endocrine disrupting properties

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

13.1.1. Product/Packaging disposal

Waste codes/waste designations according to EWC/AVV

Waste code product

16 01 14 * antifreeze fluids containing hazardous substances

*: Evidence for disposal must be provided.

Waste code packaging

15 01 02 Plastic packaging

Waste treatment options

Appropriate disposal / Product:

Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information

Land transport (ADR/RID)

Inland waterway craft (ADN)

Sea transport (IMDG)

Air transport (ICAO-TI / IATA-DGR)

14.1. UN number or ID number

UN 1170

UN 1170

UN 1170

UN 1170

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 10/11

Scheibenenteiser

Land transport (ADR/RID)	Inland waterway craft (ADN)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.2. UN proper shipping name			
ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)	ETHANOL (ETHYL ALCOHOL) or ETHANOL SOLUTION (ETHYL ALCOHOL SOLUTION)
14.3. Transport hazard class(es)			
 3	 3	 3	 3
14.4. Packing group			
II	II	II	II
14.5. Environmental hazards			
No	No	No	No
14.6. Special precautions for user			
Special Provisions: 144 601 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E2 Hazard identification number (Kemler No.): 33 Classification code: F1 Tunnel restriction code: (D/E)	Special Provisions: 144 601 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E2 Classification code: F1	Special Provisions: 144 Limited quantity (LQ): 1 L Excepted Quantities (EQ): E2 EmS-No.: F-E, S-D	Special Provisions: A3 A58 A180 Limited quantity (LQ): Y341 Excepted Quantities (EQ): E2

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU legislation

Directive 2004/42/EC on the limitation of emissions of volatile organic compounds:

Volatile organic compounds (VOC) content in percent by weight: 0.84 weight-%

15.1.2. National regulations

No data available

15.2. Chemical Safety Assessment

No data available

SECTION 16: Other information

16.1. Indication of changes

No data available

16.2. Abbreviations and acronyms

No data available

16.3. Key literature references and sources for data

No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 (REACH)

Revision date: 11 Dec 2023

Print date: 8 Nov 2024

Version: 1



Page 11/11

Scheibenenteiser

16.4. Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

Hazard classes and hazard categories	Hazard statements	Classification procedure
flammable liquids (<i>Flam. Liq. 1</i>)	H224: Extremely flammable liquid and vapour.	On basis of test data.
Serious eye damage/eye irritation (<i>Eye Irrit. 2</i>)	H319: Causes serious eye irritation.	Calculation method.

16.5. List of relevant hazard statements and/or precautionary statements from sections 2 to 15

Hazard statements	
H225	Highly flammable liquid and vapour.
H302	Harmful if swallowed.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.

16.6. Training advice

No data available

16.7. Additional information

No data available